



INSTABILITY INDEX

DESTABILIZATION DETECTION

PHASE SEPARATION DYNAMICS

MEAN PARTICLE SIZE VARIATION



# BeScan Lab


Stability Analyzer

STABILITY  
EXCELLENCE  
WITHIN REACH

**Bettersize**  
BETTER PARTICLE SIZE SOLUTIONS

# BeScan Lab

BeScan Lab, the versatile, sensitive, and reliable stability analyzer based on Static Multiple Light Scattering (SMLS) technology, is widely used in the formulation development and product quality control. It accommodates a wide range of sample concentrations up to 95% v/v and types such as emulsions, suspensions, and foams, with temperature scanning capabilities reaching up to 80 °C. BeScan Lab provides both qualitative analysis and quantification of destabilization, helping you monitor long-term product stability and achieve optimal shelf life.



## BeScan Lab Provides

- Instability index ( $I_{US}$ )
- Mean particle size
- Hydrodynamic analysis
- Radar chart for regional  $I_{US}$
- Temperature trend testing
- Particle migration rate

## Features & Benefits

### Non-destructive stability analysis for various dispersions

- Non-contact, non-dilution, non-shearing
- Sample volume fraction up to **95%**
- Particle size measurement range from **0.01** to **1,000**  $\mu\text{m}$

### Fast and direct stability measurement

- The high-performance system allows capture of subtle variations with a **20-micron** scan step
- **“One-to-many”** system enables simultaneous measurement of up to 10 samples
- Temperature control up to **80 °C** to accelerate destabilization

### Qualitative and quantitative stability results

- Identification of various unstable phenomena, such as creaming, sedimentation, flocculation, coalescence, and phase separation
- Quantification of destabilizations and study of kinetics

## From Raw Materials to Finish

BeScan Lab plays a crucial role throughout the product lifecycle, supporting formulation, production, and pre-use stages. It enables formulation optimization, quality control during manufacturing, investigation into optimal transportation and storage conditions, and research on redispersibility.



**01**  
**Research and development**  
Ensure excellent dispersibility and uniformity through raw material selection.



**02**  
**Production and quality control**  
Optimize production processes, including method, time, and temperature, to enhance efficiency.



**03**  
**Storage and transportation**  
Evaluate formulation stability under varying environmental conditions, observing destabilization, and predict shelf life.



**04**  
**Pre-use treatment**  
Study the reversibility of destabilization and compliance with usage standards.

# ADVANCED MEASUREMENT PRINCIPLE

## Static Multiple Light Scattering


Static Multiple Light Scattering (SMLS) is an optical technique used to directly characterize native concentrated liquid dispersions. This technique emits light into the sample, where it is scattered multiple times by particles or droplets before being detected.

BeScan Lab applies SMLS using an 850 nm LED as light source, with detectors set at 0° for capturing transmitted light and at 135° for backscattered light. This setup scans the sample vertically, analyzing the transmitted light for transparent systems, while the backscattered light is ideal for opaque systems.

The signals are collected at 20 μm intervals, which enables precise observation of changes in size ( $d$ ) and concentration ( $\phi$ ) of suspended materials.

### Signal display

Customized scanning procedures allow presentation of scans with different colors corresponding to different scanning times. The overlap of scans demonstrates how signals diverge from the reference as they vary with height and time. Intuitively, the scans capture local changes that characterize unstable phenomena.



The example illustrates that during sedimentation, the backscattered signals (dBS) undergo a distinctive pattern of change: a decrease at the top and an increase at the bottom, which is attributed to the migration of particles.

Light source

Backscattering detector

Transmission detector

$$I_{BS} \propto \sqrt{\frac{3\phi(1-g)Q_s}{2d}}$$

$$I_T = I_{T_0} \exp\left[-\frac{3\phi Q_s r_i}{d}\right]$$

### Features

- Versatile measurement**  
 No limitations on color or viscosity, and suitable for a wide range of samples from low to high concentrations (up to 95% v/v).
- Non-destructive and in situ**  
 Measures without preparation, thus preserving the sample's original characteristics.
- Wide particle size range**  
 Capable of measuring particles from 0.01 to 1,000 μm.
- Applicable to various systems**  
 Suitable for emulsions, suspensions, foams, and other dispersions, providing robust and high-resolution measurements.

$d$ : Mean particle size  
 $\phi$ : Volume fraction  
 $r_i$ : The radius of the sample cell  
 $Q_s$  and  $g$  can be obtained using Mie theory

# DEDICATED SOFTWARE


## for Superior Qualitative and Quantitative Stability Outcomes

### Qualitative Analysis - Identification of Destabilization

BeScan Lab utilizes near-infrared light and a precise 20-micrometer spatial resolution to detect early-stage destabilization phenomena like phase separation, sedimentation, creaming and aggregation (flocculation, coalescence, and coagulation) well before they are visually observable.


**Flocculation** often results in uniform changes in transmitted or backscattered signals across the entire sample height.

- Common in wastewater treatment, electrode slurries, and drilling fluids.




**Phase separation** typically involves evolving interfaces between phases over time.

- Common in paints and coatings, cosmetics.




**Sedimentation** causes a decrease in backscattered signals at the top and an increase at the bottom in opaque samples.

- Common in slurries, pigments, pesticides, vaccines, and body lotions.




**Creaming** in opaque samples enhances backscattered signals while lowering bottom signals.

- Common in milk-based beverages, lipid emulsions, and pesticides.




### Phase separation dynamics and mean particle size

Hydrodynamic analysis reveals layer thickness and particle migration rate over time, thereby determining the hydrodynamic mean diameter.



### Optical analysis and mean particle size variation

Particle size variation analysis is achievable with BeScan Lab, correlating transmitted and backscattered light signals.




### Quantitative Analysis - Instability Index for Rating Guide

BeScan Lab provides the instability index ( $I_{US}$ ), which quantifies the stability of dispersions. The calculation involves summing all signal variations across the entire sample height and over time, capturing all subtle variations within the sample.

This facilitates sample comparison, as a greater instability index ( $I_{US}$ ) indicates lower stability. An instability index is automatically calculated after every scan using the following formula:

$$I_{US} = \sum_n \frac{\sum_h |I_n(h) - I_{n-1}(h)|}{H}$$


BeScan Lab offers instability indices over time to compare the stability of different samples. A slower increase in the instability index indicates higher dispersion stability, resulting in a flatter curve. Analyzing the trend allows for predicting long-term stability.



### "One-to-many" system - Solution to simultaneous measurement of samples

Simultaneous measurements of up to 10 samples are possible, controlled by a single software interface.


Our "One-to-many" system saves time and adds measurement flexibility as each BeScan Lab can be controlled independently.



Control of up to 10 instruments


### Temperature trend measurement

Programmable temperature trend measurement up to 80°C, which explores stability under extreme conditions and accelerates destabilization.



### Radar chart

Global and regional instability indices for each scanning are illustrated in form of a radar chart, intuitively providing a way to investigate regional stability (top, middle, and bottom).





# VERSATILE APPLICATIONS

for Diverse Real World Cases

## Beer Foam Stability

Beer foam stability is key to quality and freshness. BeScan Lab analyzes this stability by capturing changes in transmitted signals, revealing the impact on foam transmission and the progression of the instability index. These insights aid in formulating the best beer recipe for market success.



Sample	#1	#2	#3
Alcohol content (vol%)	9	5	3
Wort concentration (*P)	18	12	8



- Sample #1 with the highest alcohol content and wort concentration is the most unstable.
- Sample #2 with average alcohol content and wort concentration is the most stable.

## Ibuprofen Suspension Redisperison Stability

Ibuprofen suspension is a widely used pain reliever whose active ingredients may settle after storage. Stability after redispersion is strongly associated with its effectiveness. BeScan Lab provides a convenient way to evaluate redispersibility.

Sample	Zeta potential (mV)	Particle size (µm)	Viscosity (mPa·s)
#1	-14.62	D <sub>10</sub> =19.38, D <sub>50</sub> =38.57, D <sub>90</sub> =57.74	55.30
#2	-6.03	D <sub>10</sub> =21.56, D <sub>50</sub> =51.11, D <sub>90</sub> =118.90	223.00
#3	-26.39	D <sub>10</sub> =12.74, D <sub>50</sub> =67.96, D <sub>90</sub> =228.20	16.80

Zeta potential is measured by BeNano 180 Zeta Pro.  
Particle size is measured by Bettersizer 2600.



- High viscosity, high zeta potential, and small particle size are beneficial to stability.
- Ibuprofen #1 with small particle size, medium zeta potential, and proper viscosity is the most stable.

## Typical Applications

Agrochemicals



Battery and Energy



Ceramics



Home and Personal Care



Food and Beverage



Petrochemicals



Pharmaceuticals



Paints, Coatings and Inks



## Accessories



**Coring cell**

Coring cells are applied with a centrifuge, which is a solution to highly viscous samples with poor-quality meniscus, such as paste, cream, and foam.



**Centrifuge**

Up to 4 samples can be handled with a centrifuge to flatten its top by means of centrifugal force. The maximal rotational speed is 5,000 rpm.



**Low-volume sample cell**

Low-volume sample cells are suitable for valuable samples or samples with small volumes. Measurement can be performed with a minimum volume of 2 mL.

# COMPREHENSIVE STABILITY ANALYSIS SOLUTIONS

## BeScan Lab

Monitoring product stability throughout the entire product lifecycle. Whether used independently or in combination with other instruments, BeScan Lab ensures product quality, process stability, and safety.



## BeNano Series

Nanoparticle size  
Size distribution  
Zeta potential  
Rheological properties



## BetterPyc 380

Powder density  
Liquid density  
Slurry solid content



## Betztersizer ST

Particle size  
Particle size distribution  
0.1  $\mu\text{m}$  - 1,000  $\mu\text{m}$



## Betztersizer 2600

Particle size  
Particle size distribution  
0.02  $\mu\text{m}$  - 2,600  $\mu\text{m}$



## Betztersizer S3 Plus

Particle size  
Particle size distribution  
0.01  $\mu\text{m}$  - 3,500  $\mu\text{m}$



## Internal Factors

### Formulation and physical properties challenge

It is challenging to select the optimal raw materials and determine the concentrations of additives, ensure high-quality raw materials, achieve compatibility among formulation components, optimize the mixing process, and manage physical properties like density to maintain stability during storage and application.

### Our solution

Combine **BeScan Lab** with **BeNano Series**, **Betztersizer Series**, and **BetterPyc 380**.

- BeScan Lab facilitates the screening and optimization of formulation components, guaranteeing superior product development.
- The BeNano series, Betztersizer series, and BetterPyc 380 collectively measure particle size, zeta potential, and density. These instruments provide comprehensive particle data, enabling the identification and control of key internal factors affecting formulation stability, thereby optimizing product performance and longevity.

## External Factors

### External forces challenge

Mitigating the impact of stirring, oscillation, and transportation to prevent destabilization.

### Environmental conditions challenge

Controlling the effects of temperature, humidity, and light exposure to prevent degradation and maintain quality.

### Our solution

Use **BeScan Lab** with **Betztersizer** and **BeNano Series**.

- BeScan Lab evaluates the stability of a system under environmental conditions throughout its distribution, storage, display, and usage, assessing the impacts of external forces on the system's stability.
- The Betztersizer and BeNano series provide essential data on particle size effects influenced by external forces, crucial for maintaining product safety, compliance, and consistency, and ensuring quality through precise control that meets industry standards and regulatory requirements.

## Specifications

Measurement principle	SMLS (Static Multiple Light Scattering)
Detection angle	0° transmission and 135° backscattering
Light source	850 nm LED
Scan step	20 µm
Scan height	0 - 60 mm
Maximal number of simultaneous samples	10*
Maximum volume fraction*	95%
Measurement range of particle size	0.01 - 1,000 µm**
Temperature control	RT - 80 °C (± 0.5 °C )
Sample volume	2 - 25 mL
Measurement mode	Regular / Fixed point / Temp. trend
Dimension	460 (L) x 260 (W) x 280 (H) mm
Weight	13.5 kg
Power supply	AC100 - 240 V, 50 - 60 Hz, 3.8 A
ISO compliance	ISO / TR 18811:2018, ISO / TR 13097:2013 ISO / TS 21357:2022, ISO / TS 22107:2021

\* Number of instruments dependent

\*\* Sample and sample preparation dependent

**Bettersize**  
BETTER PARTICLE SIZE SOLUTIONS



BREAKING  
BOUNDARIES  
SHAPING  
THE FUTURE

### Bettersize Instruments Ltd.

No.9, Ganquan Road, Jinquan Industrial Park,  
Dandong, Liaoning, China

Postcode: 118009

Tel: +86-755-26926582

### Bettersize Inc.

3188 Airway Ave, Suite K-2, Costa Mesa,  
CA 92626, United States

Tel: +1 833-699-7493 (SIZE)

info@bettersize.com  
www.bettersizeinstruments.com



Visit Our BeScan Lab Site



Visit Our Official YouTube Channel

**Disclaimer:** By using or accessing the brochure, you agree with the Disclaimer without any qualification or limitation. Diligent care has been used to ensure that the information in this brochure is accurate, Bettersize Instruments Ltd. shall not be liable for errors contained herein or for damages in connection with the use of this material. The information on this brochure is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. Bettersize Instruments Ltd. reserves the right to modify, alter, add and delete the content outlined in the brochure without prior notice and without any subsequent liability to the company.

Copyright: © 2025 Bettersize Instruments Ltd. | All Rights Reserved  
13.1300.00.02